

imu Peripheral Products



WATCHING THE
IMU POS · KIOSK
imupos.com



MSR



Card Reader Interface type
RJ11 (RS232 Level, Power Pin 1 +5V)



MSR
Supplied 1,2,3 Track



Interface
RS-232



Sound
Buzzer



Operating Temperature
0 °C to +50 °C



Power Input
DC 5V



Card Reader Interface type
RJ50 (RS232 Level, Power Pin 1 +5V)



Display Type
FSTN LCD



Brightness
500 cd/m²



Display Color
Navy Blue



Interface
RS-232



Number of Characters
20 columns x 2 lines



Character Size
8x16 Dot Matrix



Operating Temperature
0 °C to +50 °C



Input Voltage
DC 5V

Customer Display





Card Reader Interface type
DB9(RS232 Level, Power Pin 9 +5V)



Data Protocol
1-Wire®



Interface
RS-232



Operating Temperature
0 °C to +50 °C



Power Input
DC 5V

Dallas Reader



RFID Reader



Card Reader Interface type
DB9(RS232 Level, Power Pin 9 +5V)



Transmit Frequency
125 kHz standard



Transponder
H4001 / H4002 / EM4100 / 4102
EM Card Read only



Reading Distance
Up to 5 cm with EM card



Interface
RS232



Operating Temperature
0 °C to +50 °C



Power Input
DC 5V

