

21.5 POS SYSTEM

200B

Now, enjoy bigger and clearer
The 21.5-inch wide display can realize the visual effects that users need through a high-quality screen.

21.5" WIDE DISPLAY




Slim bezel



Speaker

LED lamp



- FHD resolution
- Internal speaker
- Black Slim Bezel
- LED back light
- Both landscape and portrait views are available
- Colors: White and Grey


CONTACT US

+82-2-6105-7261/7271

sales2@imupos.com





WATCHING THE
IMU POS · KIOSK
imu.com



VARIOUS I/O INTERFACE PROVIDED

- ✓ Various serial port
- ✓ Wide rooms between I/O ports
- ✓ Multi display available (3 Products)



Specification

S-200BAL		N-200B		E-200B	
System					
Processor	12th Generation Intel® Core™ Processors Core i3-1215U /Core i5-1235U / Core i7-1255U (Fanless)		Intel® Processor N97, up to 3.60 GHz (Fanless)		Intel® Celeron® Quad-core Processor J6412 2.0GHz/2.6GHz
Chipset / BIOS	Intel® Alder Lake SoC / AMI UEFI				Intel® Elkhart Lake SoC / AMI
Storage	2.5" SATA III SSD 128GB (SSD 256/512GB, optional)				
Memory	4GB SO-DIMM		8GB SO-DIMM		4GB SO-DIMM
	DDR4 3200MHz x 1 (Max 32GB, optional)		DDR4 3200MHz x 1 (Max 16GB, optional)		DDR4 2666MHz-3200MHz x 1 (Max 32GB, optional)
Graphics	Intel® Iris® Xe Graphics		Intel® UHD Graphics		Intel® UHD Graphics for 10th Gen Intel® Processors
Multi Mointor	3 (# of Displays Supported) – up to 3 monitors (optional)				
OS	Windows 10 IoT Enterprise(64bit), Windows 11(64bit)				
Display					
Primary Display Type	21.5" WLED Backlight (1920 x 1080 Resolution / 16:9 Ratio)				
Touch	PCAP 10 Point Multi-touch				
I/O Interfaces					
Rear Top & Bottom Ports					
USB	2 x USB 2.0 (Rear Top x 2), 1 x USB 2.0 (RJ11), 4 x USB 3.0 (Rear Bottom x 4)				
Serial	6 (DB9 x 3, RJ50 x 2, RJ11 x 1)				
Audio	1 x Audio-out / 3.5mm				
Extend Displays	1 x DP output, 1 x HDMI output (optional)				
LAN	1 x RJ45 (Base-T 10,100,1000m/bps Ethernet)				
Speaker	3W x 2				
Peripheral Options					
Secondary Display	• LCD Type: 9.7" or 15" LCD (USB Port x 1) • Touch Monitor: 9.7" or 15" LCD with Capacitive Touch (USB Port x 1) – by single cable(no power & USB cable)				
Customer Display (CDP)	FSTN LCD Type(20 columns x 2 lines)				
Card Reader (MSR)	Magnetic Stripe Reader: ISO 7811 ID-1 All tracks *Interface: USB(HID) and RS232C(COM6)				
Dallas Reader	Dallas Reader(i-button): 6 characters / prefix and suffix *Interface: USB(HID) and RS232C(COM6)				
Physical Dimension					
Dimension (W x D x H)	524 x 251 x 386 (mm)				
Weight	6.5 kg				
Box Dimension					
Dimension (W x D x H)	585 x 300 x 430 (mm)				
Weight	8.9 kg				
Environment					
Power Supply	DC 12V/7A (AC 100V~240V, 84W)		12V DC input (AC 100V~240V, 60W)		
Temperature	Operating Temp : 0~40℃ / Storage Temp : -20~60℃ / Humidity: 20% to 90%				
Certifications	CE, FCC, KC				

* Specifications are subject to change without prior notice. *The weight of the box varies depending on the components and the main board. (includes box weight)



☎ #609, 115, Gasan digital 2-ro, Geumcheon-gu, Seoul, 08505, Republic of Korea
☎ +82-2-6105-7261/7271 ✉ sales2@imupos.com 🌐 imupos.com

WATCHING THE
IMU POS · KIOSK

